

90CBG14FE

CUCINA 4 FUOCHI GAS SU FORNO ELETTRICO

4 BURNERS GAS RANGE ON ELECTRIC OVEN

## Caratteristiche

## Features

Piano di lavoro in acciaio inox AISI 304 | Griglie del piano in ghisa vetrificata | Bacinelle raccogliogocce del piano estraibili in acciaio inox AISI 304 stampate ad angoli arrotondati | Bruciatori in ghisa vetrificata con spartifiamma in ottone a doppia corona a fiamma stabilizzata (2 x 4,5 kW, 2 x 10,0 kW) | Rubinetti valvolati con fiamma pilota per l'accensione del bruciatore | Forno elettrico GN 2/1 riscaldato da resistenze corazzate INCOLOY indipendenti regolate da termostati regolabili da 50° a 300°C | Termostato di sicurezza a riarmo manuale | Guide reggigriglie a tre posizioni ed estraibili per la completa pulizia della camera | Pannello comandi facilmente estraibile per facilitare le operazioni di pulizia e manutenzione | Scarico fumo in ghisa rimovibile | Piedini in acciaio inox regolabili in altezza

Work top in AISI 304 stainless steel | Top grids are in vitrified cast iron | Removable drip-collecting trays in AISI 304 stainless steel with rounded corners | Burners in vitrified cast iron with burner cap in brass with double ring and stabilized flame (2 x 4,5 kW, 2 x 10,0 kW) | Valve tap with pilot flame for gas burner ignition | Electric oven GN 2/1 heated by independent INCOLOY armoured heating elements controlled by thermostats regulating from 50° to 300°C | Safety thermostat with manual reset position shelf runners which can be removed for thorough oven cleaning | 3-position shelf runners which can be removed for thorough oven cleaning | Control panel which can be quickly removed for easy cleaning and maintenance | Removable vitrified cast iron exhaust grate | Adjustable AISI 304 stainless steel feet



MODELLO  
MODEL



DIMENSIONI mm  
DIMENSIONS mm



POTENZA GAS KW  
GAS POWER KW



ALIMENTAZIONE  
FEEDING



ALLACC. GAS  
GAS CONNECTION

VOLUME m<sup>3</sup>

PESO Kg  
WEIGHT Kg

POTENZA ELETTRICA KW  
ELECTRIC POWER KW





-

-

-

ALLACC. ELETTRICO  
ELEC. CONNECTION

VAC400-3N 50/60Hz



E = Allacciamento elettrico  
Electrical connection

G = GAS 1/2"