

90BRE15I

| BRASIERA RIBALTABILE ELETTRICA, VASCA INOX DA 150 LT.

| ELECTRIC TILTING BRATT PAN, STEEL TANK 150 LT.

| Caratteristiche

| Features

| Struttura esterna e coperchio in acciaio inox AISI 304 | Coperchio incernierato posteriormente e bilanciato a molla | Ribaltamento manuale della vasca ottenuto mediante volantino in materiale termostatico e vite senza fine | Vasca con pareti in acciaio inox AISI 304 e fondo in acciaio inox di grosso spessore | Rubinetto carico acqua | Resistenze corazzate INCOLOY a diretto contatto del fondo esterno termodiffusore della vasca | Regolazione termostatica della temperatura da 50° a 300°C | Termostato di sicurezza a riarmo manuale | Scarico fumo in ghisa rimovibile | Piedini in acciaio inox regolabili in altezza

| External structure and lid in AISI 304 stainless steel | Lid hinged at the back and counter-balanced

| Manual tipping of the tank by means of hand wheel in thermoplastic material and self-tapping screw

| Tank with walls in AISI 304 stainless steel and bottom in AISI 304 stainless steel | Water-filling tap

| INCOLOY armoured heating elements in direct contact with the heat-radiating external bottom of the tank

| Thermostatic regulation of the temperature from 50° to 300°C | Safety thermostat with manual reset

| Removable vitrified cast iron exhaust grate | Adjustable AISI 304 stainless steel feet



MODELLO
MODEL



DIMENSIONI mm
DIMENSIONS mm



POTENZA ELETTRICA KW
ELECTRIC POWER KW



VOLUME m³



PESO Kg
WEIGHT Kg



ALIMENTAZIONE
FEEDING



ALLACC. ELETTRICO
ELEC. CONNECTION

90BRE15I

1200x900x950

14,8

1,8

245

400 V

VAC400-3N 50/60Hz

A = Carico acqua ø 12 mm
Water supply ø 12 mm
E = Allacciamento elettrico
Electric connection

